

HKJC Amphitheatre - Venue Information 香港賽馬會演藝劇院 - 場地資料

Auditorium 觀眾席	Stage 舞台	Lighting 燈光	Sound 音響	Projection 投影	Others 其它
Continental Seating- - with three sides audiences Raked Floor- 沿斜地面 - - U shape seating platform Seating Capacity 600 nos.- 座位總數 - - 600 seats from row A to H - include 4 wheelchair seats in row A <i>Wheelchair entrance is at the backstage entrance on ground floor (輪椅使用者請從後台出入口進場)</i>	Thrust Stage- 三向舞台 - - Flat floor stage Floor Surface- 台面結構 - - Beech timber dance floor - Floor loading (500kg/m ²) Performing Area- 演出面積 - - U shape stage about 16m(W) x 17m(D) Permanent Installation- 固定裝置 - - Tunable acoustics via reversible reflective / absorptive panels at rear of auditorium Suspension System- 懸掛系統 - - One 16m motor bar in front of timber back wall top height 8.2m above stage floor <i>(Total SWL 500kg)</i> - Four fixed lighting bars installed along slope ceiling truss <i>(Total SWL 500kg each)</i> - Two fixed lighting bars installed along two wings above rear of auditorium <i>(Total SWL 1000kg each)</i> Get In- 入票 - - Loading dock entrance 1m(W) x 2.2m(H) at back of stage right - Sliding timber wall panel to allow get in of long scenery items Stage Equipment- 舞台配備 - - Musician chair x 80 nos. Music stand x 80 nos. - "Genie" aerial work platform AWP-40S Max platform height: 12m <i>(Only for trained person and must have venue approval)</i> <i>(須要場地管理之允許及有操作經驗者方可使用)</i>	Control- 控制室 - - Room located in auditorium - rear center Console- 調控台 - - ETC EOS Apex 5 (24K) Lighting Console Dimmer Control- 調光器 - - ETC Sensor3 HSR 60 way 3kW dimmer / relay racks with ThruPower Modules: 60 x 3kW Control Patch- 接駁控制 - - Mains patch individually LED Luminaires- LED 燈類 - - Standard Rig re plan - GLP X5 LED Moving Wash x 16 for OH - ETC / Halcyon Titanium Ultra Bright LED Moving Light x 22 for OH / Auditorium two wing Fix bar - ETC Source 4 LED Lustr 8 w XDLT 26° x 20 for FOH - ETC Source 4 LED Lustr 8 w XDLT 36° x 12 for OH - ETC Source 4 LED Lustr 8 w XDLT 15°-30° Zoom x 12 for OH ETC / ColorSource Linear 2 x 9 for CYC Lights Follow Spot- 追光 - Robert Juliat Manon 1.2kW HMI x 2 Lighting Position- 燈光位置 - Four fixed lighting bars installed along slope ceiling truss <i>(Max rigging height above stage floor: 11m)</i> Two fixed lighting bar installed along two wings above rear of auditorium <i>(Rigging heights from 2.95m to 3.5m)</i> Auxiliary Power Supplies- 輔助供電 - 220V 50Hz (Single Phase) Control Room 63Amps - 3 phase Connection - Terminals Require: WR1 issued by REW & REC <i>(需要電業工程人員及承辦商簽發WR1)</i> REW (Registered Electrical Worker) REC (Registered Electrical Contractor)	Control- 控制室 - - Room located in auditorium - rear center House Console- 主調音台 - - Yamaha QL5 Digital Mixing Console - Local In & Out: 32 in & 16out - Input channels to mix: 64 mono and 8 Stereo - Busses: 16 mix and 8 matrix - Fader: 32+2 Signal Processing Equipment- 訊號處理器材 - - BSS FCS960 equalizer - BSS DPR series comp/ limiter - Lexicon PCM70 reverb unit - XTA GQ600 equalizer - Yamaha SPX990 multi-effect processor Playback Equipment- 重播設備 - - Tascam CD-01U PRO professional CD player - Tascam SS-CDR200 Multi-media player/ Recorder Microphone- 麥克風 - DYNAMIC - 動圈式 - - AKG: D12VR, D541E, D90S - AUDIX: D4, OM6 - Electro-Voice: RE-20 - Sennheiser: BF 531, e 835-S, MD 421, MD 422, MD 738FE - Shure: Beta 57A, Beta 58, SM57, SM58 CONDENSER - 電容式 - - AKG: CK1, GN30, GN50 - AUDIX: M1250 - DPA: dfacto II FA4018, SC4098-BX45, 4099, 2011C - Neumann: KM140, KM184 - Ramsa: WM-S5E - Sennheiser: BF 5032 - Shure: SM85, SM87 Wireless Microphone - 無線麥克風 - - Sennheiser Evolution 500 series with <i>(Lavalier or Handheld Microphone)</i>	Control- 控制室 - - Room located in auditorium - rear center Projection Screen- 投影幕 - Oray Matt White electric roller screen Size: 11m(W) x 7.5m(H) - Maximum image size: for 4:3 format: 10m(W) x 7.5m(H) for 16:9 format: 10.8m(W) x 6m(H) Projector lift location- 投影機升降台位置 - At rear centre of auditorium ceiling Throw distance: 23.5m - SVS 7 Series lift platform for projector: - Max. size: 0.75m(W) x 1.2m(D) x 0.6m(H) - <i>(Max. SWL 150kg)</i> Power outlet: Ceenorm 32A single phase	Dressing Rooms- 化粧間 - - With access codes door locks 配備密碼門鎖 - Accommodating 14 persons with - Dressing room A for 7 persons at SR (25m ² /269ft ²) - Dressing room B for 7 persons at SL (22m ² /237ft ²) Artists' Facilities- 表演者設施 - - Show relay / cast call paging - En suite shower & toilet in dressing rooms - CCTV monitor viewing stage
The Academy reserves the right to amend or update venue facilities without notice. 演藝學院保留更改及更新場地設施的權利，恕不另行通知。 # Optional equipment for which an additional daily hire charge will apply. # # 選擇性器材及需要額外日租計算# ** These items are shared amongst several venues - their availability for a particular hiring is at the management's sole discretion. ** 此等項目分配於各場地使用-場地管理就個別租用者要求而提供可使用的數量。					

HKJC Amphitheatre - Venue Information 香港賽馬會演藝劇院 - 場地資料

Auditorium 觀眾席

Stage 舞台

Lighting 燈光

Sound 音響

Projection 投影

Others 其它

Fixed House PA System-
固定揚聲系統 -
 - four d&b audiotechnik CCL12 line arrays and one CCL-Sub Subwoofer for each auditorium zone

**** Mobile Speakers-**
流動揚聲器 -
 - Fender: SPL-1282
 - Sound Project: X-act self-powered monitor

Communication-
劇院通訊系統 -
 - Intercom system available at all control points
 - Telex wireless intercom system
 - Cast call paging system to dressing rooms
 - Infrared monitor viewing stage
 - CCTV monitor viewing stage at control room, backstage, dressing rooms
 - CCTV monitor in audiences lobby for latecomer

The Academy reserves the right to amend or update venue facilities without notice.
 演藝學院保留更改及更新場地設施的權利, 恕不另行通知。

Optional equipment for which an additional daily hire charge will apply.#

選擇性器材及需要額外日租計算#

** **These items are shared amongst several venues - their availability for a particular hiring is at the management's sole discretion.**

** 此等項目分配於各場地使用-場地管理就個別租用者要求而提供可使用的數量。