Lyric Theatre - Venue Information 歌劇院 - 場地資料

Auditorium 觀眾席	Stage 舞台	Lighting 燈光	Sound 音響	Projection 投影	Others 其它
Continental Seating in Circle and-	Proscenium Stage-	Control-	Control-	** Projection Screens-	** Dressing Rooms-
Gallery, Stalls seats divided by-	鏡框舞台 -	控制室 -	控制室 -	投影幕 -	化粧間 -
two aisles-	- Flat floor with 2 forestages lifts for	- Room located in auditorium - circle rear left	- Room located in auditorium - stalls rear center	# EZ Folo portable (Front or Rear) 25'(W) x 18'(H) #	** Subject to availability
Raked Floor-	small / large pit / thrust stage	Console-	House Console-		供求視乎實際情況
沿斜地面 -	Floor Surface-	調控台 -	主調音台 -		- Equip with access codes locks
Full Seating 1,181 nos	台面結構 -	- ETC EOS Apex 10 24K with	- DiGiCo Quantum 338 Digital Mixing Console		配備密碼門鎖
座位總數 -	- Hardboard over sprung T & G floorboards	moving light control / effects	128 Input channels, 58 Aux / Sub-Group Busses		- Accommodating 89 persons total
- Stalls 466 nos.	- Stage floor loading (500kg/m²)	- Back up system	18 x 18 Matrix out		- No.1-5 stage level stage right
- Circle 274 nos.	Dance Flooring-	ETC EOS Titanium (Eos Ti™) 24K with	- 2nd Console DiGiCo Quantum 388		- No.7-14 below stage level with
- Gallery 441 nos.	跳舞地膠 -	moving light control / effects	last two row of auditorium stalls level		staircase access to both sides
- Pit 2 used 1,143 nos.	- Grey / Black mat	Dimmer Control-	- Control room SD-Rack Layout:		- DR1 for 3 persons(19m²/205ft²)
- Pit 1 + Pit 2 used 1,093 nos.	Proscenium Opening-	- 調光器 -	48 analog inputs, 32 analog outputs, 4 ln & 4Out AES		- DR2 for 2 persons(17m²/180ft²)
- 4 wheel-chair spaces at circle	台口面積 -	- Strand STM 390 dimmers	- Two floating SD-Rack at Stage/Pit:		- DR3 for 5 persons(26m²/278ft²)
•	- Variable 12.8 - 18m(W) x 6 - 9m(H)	- ETC Sensor3 ThruPower dimmers x 40	32 analog inputs, 16 analog outputs		- DR4 for 2 persons(17m²/180ft²)
	- Stage floor 0.9m above auditorium floor	- Total: 8 x 10kW, 92 x 5kW, 330 x 2kW	- One floating Mini-Rack:		- DR5 for 2 persons(14m²/150ft²)
	Forestage-	Control Patch-	16 analog inputs, 8 analog outputs, 4 In & 4Out AES		- DR7 for 4 persons(24m²/260ft²)
	幕前副台 -	- 接駁控制 -	- Signal Processing Equipment-		- DR8 for 6 persons(25m²/270ft²)
	- Depth of apron in front of the	- At switchboard	- 訊號處理器材 -		- DR9 for 4 persons(20m²/220ft²)
	setting line 2.08m or 4.48m	- Mains patch individually	- BSS FCS960 equalizers		- DR10 for 13 persons(51m²/553ft²)
	Orchestra Pit-	Lektriflex multicore at Gallery	- BSS DPR series comp/ limiters		- DR11 to 14 for 12 persons each
	樂池 -	Luminaires-	- Lexicon PCM70 reverb unit		(around 50m²/538ft² each)
	- 15.6m(W) x 3.5m(H) x 6.1/3.5m(D)	燈類 -	** XTA GQ600 equalizers		Artists' Facilities-
	accommodating 60 / 30 persons	- FOH-	Yamaha SPX990 multi-effect processor		- 表演者設施 -
	88 / 38 seats lost through use	- ETC Source Four 750W 10° x 22	- Playback Equipment-		- Show relay / cast paging
	Performing Area-	- ETC Source Four 750W 14° x 14	- 重播設備 -		- Showers in each room
	演出面積 -	- ETC Source Four 750W 19° x 30	** Marantz PMD331/ 340 CD player		- CCTV by arrangement
	- Main stage (主台)	- ETC Source Four Zoom 15° - 30° x 10	Tascam SS-CDR200 Multi-media player/ Recorder		- Telephone at Company Office &
	24m(W) x 16m(D) x 27m(H) to Grid	- ETC Source Four EDLT 750W 19° x 10	Microphone-		stage Right corridor
	- Rear stage (後台)	- ETC Source Four EDLT 750W 26° x 10	麥克風 -		- Laundry / Wardrobe facilities
	18m(W) x 13m(D) x 8.8m(H) to Ceiling	- Robert Juliat 710SX (10/25) 2kW x 10	- DYNAMIC-		- Quick change temporary setup
	- Side stage (側台)	Robert Juliat 714SX (15/40) 2kW x 10	- 動圈式 -		
	12.8m(W) x 14m(D) x 8.8m(H) to Ceiling	- STAGE-	- AKG: D12VR, D541E, D90S		
	Flying System-	- ETC Source Four 750W 26° x 20	- AUDIX: D4, OM6		
	吊杆系統 -	- ETC Source Four Zoom 15° - 30° x 20	Electro-Voice: RE-20		
	- 63 single purchase counterweight bars	- ETC Source Four Zoom 25° - 50° x 20	- Sennheiser: BF 531, e 835-S, MD 421,		
	4 double purchase side counterweight bars	- CCT Starlette Fresnel 1kW x 30	MD 422, MD 738FE		
	(safety loading 600kg per bar)	- CCT Starlette Fresnel 2kW x 60	Shure: Beta 57A, Beta 58, SM57, SM58		
	- 10 motorized bars	- Parcan 64 1kW x 50	- CONDENSER-		
	6 motorized bars (stage left and stage right)	- Quartz Orion 1kW G.Row x 12	- 電容式 -		
	3 motorized bars in front of the proscenium arch	Strand IRIS 4 1kW Cyc. Flood x 8	- AKG: CK1, GN30, GN50		
	(safety loading 750kg per bar)	Follow Spot-	- AUDIX: M1250	The Academy reserves the right to amend or update ve	nue facilities without notice.
	- Rear stage 5 electric winch bars	- 追光 -	Crown: PCC160	演藝學院保留更改及更新場地設施的權利, 恕不另行通知.	
	(safety loading 250kg per bar)	** Robert Juliat Cyrano 2.5kW HMI x 3	- DPA: dfacto II FA4018, SC4098-BX45,	# Optional equipment for which an additional daily hire c	harge will apply.#
	- Side stage 3 hand winch bars	Extra Luminaires-	- 4099, 2011C	# 選擇性器材及需要額外日租計算.#	
	(safety loading 250kg per bar)	-Share with other venues	- Neumann: KM140, KM184	** These items are shared amongst several venues - their	availability for a particular
	- Fixed bars at auditorium circle and gallery front	額外燈類 - 與其他場地共用	- Ramsa: WM-S5E	hiring is at the management's sole discretion.	
	(safety loading 150kg per bar)	- PROFILES-	** Sennheiser: BF 5032	** 此等項目分配於各場地使用-場地管理就個別租用者要求而提	提供可使用的數量.
	•	- ETC Source Four 750W 26° x 20	Shure: SM85, SM87		
		I ==== = = = === ===		•	V T 1.1.1

- ETC Source Four Zoom 15° - 30° x 30

ETC Source Four Zoom 25° - 50° x 20

Venue Technical Sep, 2025

Sep, 2025

Lyric Theatre - Venue Information 歌劇院 - 場地資料 Auditorium 觀眾席 Stage 舞台 Lighting 燈光

Auditorium 觀眾席 Stage 舞台 Lighting 燈光 Sound 音響 Projection 投影 Others 其它

(需要電業工程人員及承辦商簽發WR1)

	Stage 舞台	Lighting 燈光	Sound 音響	Projection 投影 Others 其它
	Permanent Attachment-	- FRESNELS-	Wireless Microphone-	
	固定裝置 -	- CCT Minuette 650W x 10	無線麥克風 -	
-	- House Curtain (line CW7)	- CCT Starlette 2kW x 6	Sennheiser Digital 6000 series	
-	- Acoustic Shell ceiling panels on line FM5, M2	ADB TVM 5000 5kW x 4	Sennheiser Evolution 500 series	
	M6, CW16, CW25, CW34, CW43 and CW52	# ARRI HMI 2.5kW Fresnel x 1 #	(Both series, with Lavalier or Handheld microphone)	
	Flying Bar Lengths (Main) -	# ARRI HMI 4kW Fresnel x 1 #	- Fixed House PA System-	
	吊杆長度 -	- PARCAN-	固定主揚聲系統 -	
١.	- 18m, extendable to 22m	- Parcan 64 1kW x 16	- Seven d&b audiotechnik Qi1 line array loudspeakers	
	Masking & Soft Hanging-	Altman Zip Strip 50W 12 Degree	plus two Qi-SUB sub-woofers per side for	
	指景帳幕及掛幕ー	- MR16 Borderlight 2'-2" x 4, 6'-4" x 9	- Main Fill Left & Right	
١.	Green velour house curtain	** Thomas Cyc. Flood 4 1kW x 5	Eight d&b audiotechnik T10 line array loudspeakers	
١.	- 2 sets black full tabs, size: 20m(W) x 10m(H)	Scenic Projection-	- for Main Centre Array	
١.	- 2 sets black half tabs, size: 12m(W) x 10m(H)	- 投影效果 -	Five d&b audiotechnik 4S full range speakers	
١.	- 6 black borders, size: 20m(W) x 5m(H)	- Pani BP-2 2kW x 4	- for Front Fill at Front of Stage	
١.	5 pairs of black legs, size: 5m(W) x 10m(H)	- Pani Effect Motor Unit for Pani BP-2 x 4	Two d&b audiotechnik 10S full range speakers	
١.	Flat cyclorama screen for front and	- Flame wheel x 2	for Upper Gallery Fill hang on Light Bridge 2	
	back projection, size: 18m(W) x 10m(H)	- Fleecy cloud wheel x 2	Two d&b audiotechnik 8S full range speakers	
l.	Black gauze & White gauze, 20m(W) x 10m(H)	- Stormy cloud wheel x 2	for Gallery Side Box Fill hang on Light Bridge 1	
	Various black masking flats	Water wheel x 2	** Six Apogee AFI-2 two-way full range speakers for	
	- SL Side masking on track	Lighting Position-	surround system (Rear) installed at rear of stalls,	
	SR Side masking on line M63, M64	と Briting F Osition - 燈光位置 -	- circle and upper gallery	
	Get in-	B元山直 - - FOH-	BSS Soundweb programmable signal processing	
	入景 -	- L / R Perches x 2		
		# L / R Slot x 6	- system with fixed EQs and system delay data	
	Through Loading Bay		- Mobile Speakers- - 流動揚聲器 -	
	Minimum dimensions (4.4m(H) max) sufficient to	- Light Bridge x 3		
	accommodate 40' container(High Cube)	Circle front and Gallery front	Apogee: ACS-2	
	Loading platform 0.95m above driveway level	- STAGE-	- Bose: 402, 32se	
	Goods lift access to all floors	- Wired spotbar x 7	Duran Audio: U-14 self-powered loudspeaker	
*	* Stage Equipment-	- Mobile ladder x 8	- Fender: SPL-1282, SPL-1285	
	舞台配備 -	** Mobile side light tower x 8	- Galaxy Audio: GHSVC monitor,	
•	- Cougar XLT 2900 hydraulic lift max. 8.8m(H)	Smoke Machines-	GPA5XD140 self-powered monitor	
•	Instant Tallescope 50518: 3.5m - 5.9m(H)	- 煙機 -	LEM self-powered loudspeaker: SPN6A, T3A,	
٠	Instant Tallescope 50524: 4.6m - 7.5m(H)	- Le Maitre MVS Hazer x 2	- T5A, T5MA, T5SA	
•	- Musician chair x 100 nos.	- Le Maitre MVS Smart Hazer x 2	Meyer Sound: UPM-1P self-powered loudspeaker	
٠	- Illuminated music stand x 60 nos.	** Smoke Factory Captain D x 4	Tannoy Wildcats series (Jaguar, Puma)	
•	Non-illuminated music stand x 90 nos.	Accessories-	Communication-	
	Piano-	- 其它配備 -	- 劇院通訊系統 -	
	鋼琴 -	- Peasouper dry ice machine x 1	- Stage Manager's desk at Stage Right with talkback	
#	Kawai Concert Grand Piano (GS100) #	- Aquafog 3300 dry ice machine x 2	- system, cue light system, cast call paging system	
	Yamaha Baby Grand Piano (C6)	- A range of Lee filters stocked	 to dressing rooms, CCTV monitor viewing stage 	
	Yamaha Upright Piano (U1A)	- UV lamp x 2	and conductor	The Academy reserves the right to amend or update venue facilities without notice.
	· Acoustic Setup	Martin Atomic 3000 DMX Strobe light x 2	Intercom system available at Theatre all control points	演藝學院保留更改及更新場地設施的權利,恕不另行通知.
١.	Orchestral Concert 18m(W) x 12m(D)	Auxiliary Power Supplies-	- Green-Go wireless intercom system	# Optional equipment for which an additional daily hire charge will apply.#
١.	Chamber Concert 14m(W) x 7.5m(D)	- 輔助供電 -	Infrared monitor viewing stage	# 選擇性器材及需要額外日租計算.#
		220V 50Hz (Single Phase)	CCTV monitors in all foyers for latecomer	** These items are shared amongst several venues - their availability for a particular
		Rear stage 300Amps - 3 phase	Auxiliary Sound Power Supplies-	hiring is at the management's sole discretion.
		Side stage 300Amps - 3 phase	音響專用輔助供電 -	** 此等項目分配於各場地使用-場地管理就個別租用者要求而提供可使用的數量.
		Connection - Bus Bars	220V 50Hz (Single Phase)	
		Require: WR1 issued by REW & REC	Side stage 32Amps - Single Phase x 2	Venue Tech
				T .

Connection - Socket